Contents

page

Abstract i
Acknowledgements iii
Contents v
List of Figures vii
List of Tables viii
List of Symbols ix
List of Abbreviations x

Chapter 1: INTRODUCTION
1.1 Brief Results, Scope, and Future Prospects of the Work 2

Chapter 2: Review of Literature
2.1 Wastewater and water pollution 5
2.2 Saline wastewater characteristics 5
2.3 Classification of saline water 6
2.4 Sources of saline wastewater 7
2.4.1 *Industrial effluent* 7
2.4.2 *Domestic effluent* 8
2.4.3 *Petroleum effluent* 9
2.4.4 *Mining effluent* 9
2.5 Effect of water salinity 10
2.6 Conventional methods for saline wastewater treatment and challenges 11
2.6.1 *Membrane technologies* 11
A. *Reverse osmosis* 11
B. *Forward osmosis* 12
C. *Membrane bioreactor* 12
D. *Membrane distillation* 13
2.6.2 *Thermal power-based technologies* 13
2.6.3 *Chemical methods for saline waste treatment* 13
2.6.4 *Biological treatments* 13
2.7 Electrochemical treatment techniques 13
2.7.1 *Electrochemical oxidation* 14
2.7.2 *Electrofloatation* 14
2.7.3 *Electrodialysis* 14
2.7.4 *Electrocoagulation* 15
2.8 MFC 15
2.9 PMFC 16
2.9.1 *Mechanism of bioelectricity generation in PMFC* 17
2.9.2 *PMFC design parameters* 17
A. *Dual v/s single chambered MFCs* 17
B. *Construction materials, electrolytes, electrodes, and separators* 18
C. *Electrode material* 18
D. *Separator* 19
E. *Effect of light intensity, temperature, dissolved oxygen (DO), CO_2, pH, and salts* 19
2.9.3 *Economic importance of PMFC* 20
2.10 Use of PMFC in the treatment of saline wastewater and organic matter removal 21

Chapter 3: Performance of Photo-microbial fuel cell with *Dunaliella salina* at the saline cathode 22
3.1 MFC arrangement and operational PMFC setup 23
3.2 Results and discussions 24
3.2.1 *Voltage profile for PMFC versus time* 24
3.2.2 *COD and DO profile of the PMFC for sustainable power generation* 25
3.2.3 *Total glycerol and lipid content* 26
3.2.4 *Polarization curve interpretation and energy output* 27
3.2.5 *Cyclic voltammetry (CV) interpretation* 29

3.2.6 *Microscopic observations* 29
3.2.7 *Inspection of hypersaline algal growth at the cathode* 30
3.2.8 *Beta (ß) carotene amount* 31
3.3 Conclusions 32

Chapter 4: Removal of organic pollutants from saline waste using *Dunaliella* and halophilic bacteria in photomicrobial fuel cell 34
4.1 PMFC construction and operation 35
4.2 Results and discussions 37
4.2.1 *Fourier transform infrared spectroscopy (FTIR) analysis of LEA biomass* 37
4.2.2 *Effect of salinity on voltage generation and other parameters* 37
4.2.3 *Effect of salinity on power generation of PMFCs* 39
4.2.4 *CV analysis* 41
4.2.5 *Effect of salinity concentration on algae growth and other value-added product production* 42
4.2.6 *Biofilm analysis of the electrodes* 45
4.2.7 *Metagenome analysis of anodic biofilm* 47
4.3 Conclusions 48

Chapter 5: Conclusions and Future Prospective 50

Annexure A: Materials and Methods 52
A.1 *Materials* 52
A.2 *Methods* 52
A.2.1 *Sample collection* 52
a) *For algae* 52
b) *For starch degrading bacteria* 53
A.2.2 *Algae cultivation* 54
A.2.3 *Lipid extraction and pre-treatment of LEA biomass* 54
A.2.4 *Analytical techniques* 54
a) *DO* 54
b) *Carbon dioxide estimation (CO_2)* 54
c) *COD* 54
d) *Algal growth estimation* 55
A.2.5 *Electrochemical analysis* 55
a) *Measurement of power density and voltage* 55
b) *CE* 55
c) *CV analysis* 55
A.2.6 *Value-added product estimation* 56
a) *Total lipid extraction* 56
b) *Glycerol estimation* 56
c) *Total Carotenoid extraction* 56
A.2.7 *FTIR* 56
a) *For LEA* 56
b) *For anodic biofilm* 56
A.2.8 *SEM* 57
A.2.9 *HPLC* 57
A.2.10 *Strain identification* 57
A.2.11 *Metagenomic analysis of the anodic biofilm* 57
A.2.12 *Statistical interpretation* 58

References 59
List of publications 69

List of Figures

Figures	*Title*	*Page*
1.1	A schematic representation of the PMFC employed in this thesis work.	*3*
2.1	Factors contributing to secondary salinization as well as groundwater contamination.	*6*
2.2	Industries responsible for the generation of the saline sewage.	*8*
2.3	Domestic effluent generation and treatment.	*8*
2.4	Effect of salinity on the ecosystem.	*11*
2.5	A typical photosynthetic microbes assisted PMFC showing power generation with various applications.	*17*
2.6	Cultivation, value-added product generation, power generation, biofuel generation, and resource recovery of algae biomass.	*21*
3.1	Schematic presentation of the strategy employed in the current study.	*23*
3.2	Schematic representation of the PMFC where 1 and 2 represent the anode and cathode, 3. proton exchange membrane, 4. external resister, 5. multimeter, 6 and 7 titanium wires, 8. algae biomass, 9. electrogenic bacteria, 10. substrate (sodium acetate) (arrows represent movement of ions).	*24*
3.3	The profile of voltage generation for 0.5 M NaCl PMFC across the external resistor 1000 Ω with time in h (arrow represents the substrate addition).	*25*
3.4	(A) Polarization curve for 0.5 M NaCl PMFC; (B) Energy obtained in the 5th batch cycle of 0.5 M NaCl PMFC is represented here as the area under the curve (shaded gray).	*28*
3.5	(A) Polarization curve for 1.0 M NaCl PMFC; (B) Polarization curve for 1.5 M NaCl PMFC; (C) Alage growth as observed in PMFC at the cathode with different salinity concentrations.	*28*
3.6	(A) CV curve of 0.5 M NaCl PMFC; (B) CV curve of 1.0 M NaCl PMFC; (C) CV curve of 1.5 M NaCl PMFC during 5th batch cycle with the voltage range of -0.7 to +0.7 V at a scan rate of 1 mV/s to 10 mV/s.	*29*
3.7	SEM images observation for (A and C) Pre-treated graphite felt electrode without biofilm, (B) Graphite felt electrode with anodic biofilm, and (D) Graphite felt electrode with cathodic biofilm.	*30*
3.8	(A) The chromatograph of standard β-carotene (column: C18 column, RT- 28.27 min); and (B) chromatograph of 0.5 M fed cathodic extract (RT- 28.26 min) (C) chromatograph of 1.0 M fed cathodic extract (RT- 28.24 min); and (D) chromatograph of 1.5 M fed cathodic extract (RT- 28.27 min).	*31*
4.1	Schematic presentation of the strategy employed in the current study.	*35*
4.2	Schematic diagram showing clay ware and plastic bucket-based low-cost PMFC.	*36*
4.3	FTIR spectrum obtained for intact algae biomass and LEA biomass.	*37*
4.4	The profile of voltage generation of all the operating PMFC across the external resistor 100 Ω with time in hours.	*39*
4.5	Polarization curve for the PMFCs at different NaCl concentrations and anodic substrates: A, B, and C with 0.5 M; D, E, and F with 1.0 M; G, H, and I with 1.5 M salinity, whereas A, D, and G fed with starch; B, E, and H with LEA; C, F, I with no substrates at the anode.	*40*
4.6	Energy obtained in the last operating batch cycle of the PMFCs is represented as the area under the curve (shaded gray) for the PMFCs at different NaCl concentrations and anodic substrates: A, B, and C with 0.5 M; D, E, and F with 1.0 M; G, H, and I with 1.5 M salinity, whereas A, D, and G fed with starch; B, E, and H with LEA; C, F, I with no substrates at the anode.	*41*
4.7	CV curve for the PMFCs at different NaCl concentrations and anodic substrates: A, B, and C with 0.5 M; D, E, and F with 1.0 M; G, H, and I with 1.5 M salinity, whereas A, D, and G fed with starch; B, E, and H with LEA; C, F, I with no substrates at the anode.	*42*
4.8	Algae growth as observed in PMFC at the cathode at different salinities.	*45*
4.9	SEM images obtained for the observation of PMFCs operated under different salinity conditions comparing 0.5 M and 1.5 M LEA-fed PMFCs, where the images A and D represent control showing pre-treated graphite felt electrodes without biofilm at 0.5 M and 1.5 M salinity respectively; B and C showing the biofilm on anodic (bacteria) and cathodic (algae) electrodes of 0.5M system respectively; E and F showing the biofilm on anodic (bacteria) and cathodic (algae) electrodes of 1.5 M system respectively.	*46*
4.10	FTIR spectrum bands (in the range of 1900–500 cm^{-1}) for type-IV pili activity in anode biofilms.	*46*
4.11	Microbial community structure under different salinity conditions comparing 0.5 M and 1.5 M LEA-fed PMFCs at (A) Phylum, (B) Class, and (C) Family level, (D) A heat map showing the taxonomic	*48*

assignment for each OUT where, intense color (Red) represents OTUs having a relatively higher abundance, whereas light color (blue) represents OTUs having a relatively lower abundance.

A.1 A. Compound microscopic image of Sambhar Lake algae *D. salina* showing characteristic shape and size and cup-shaped chloroplast (Left image); B. Fluorescence image of *D. salina* under the FITC filter (495 nm to 516 nm) (Right image). 53

List of Tables

Table	*Title*	*Page*
2.1	The classification system established by the FAO, as outlined by Rhoades et al. (1992), for the saline water categorization.	*7*
2.2	An overview of the critical characteristics of saline wastewater in the effluents discharged by various industrial sectors.	*9*
2.3	Different methods are used to remove contaminants from wastewater.	*12*
2.4	Use of MFC for the saline wastewater treatment.	*16*
4.1	Labeling of the PMFC systems used for the study based on salt concentrations and the substrate used in the anode.	*36*
4.2	Performance of the PMFC reactors operated at different salinity concentrations and substrates.	*44*
A.1	List of all the chemicals and reagents used in the complete study	*52*
A.2	The parameters of the collected water samples from the Sambhar Lake.	*53*
A.3	The parameters of the collected water samples from the Sambhar Lake.	*54*